

1

2 **[0045]** ABSTRACT OF DISCLOSURE

3 **[0046]** Invention restrains through the design of the harness, without the use or  
4 manipulation of attached cumbersome technology. Invention is a harness of three  
5 straps that is designed to easily adjust to fit the restrainee. A primary strap has two  
6 secondary left and right straps each attached to the left and right of the primary strap's  
7 center point. These two secondary left and right straps each have loops at their ends.  
8 The primary strap is placed across the restrainee's front with the secondary left and  
9 right straps brought over the shoulders (and crossed or left uncrossed) or under the  
10 axillae, depending on the placement of the primary strap. The two ends of the primary  
11 strap are brought through the loops of the secondary left and right straps. The ends of  
12 the primary strap can be threaded through each or both loops. The guardian then  
13 holds the ends of the primary strap.

14

15 **[0047]** DRAWINGS

16 **[0048]** Three pages of drawings, a total of six figures, are submitted as part of this  
17 application. To more easily conform to the requirements of MPEP 608.02, *et. seq.*, the  
18 drawings are submitted on separate sheets with appropriate identification for  
19 submission with the application.

20 **[0049]** In order to comply with MPEP 608.01(a), applicant incorporates here in the  
21 specification the three pages of drawings by reference.

22